

UNITED FIRE EQUIPMENTS PRIVATE LIMITED

Manufacturers of **LIFEGUARD** brand. ISI Marked Fire Fighting Equipments

AN ISO 9001 : 2015 CERTIFIED COMPANY

OFFICE : Lifeguard Tower, K - 960, Rithala (Opp. SBI), Rohini, Delhi -110085

WORKS : B - 38, Mangolpuri Industrial Area, Phase-II, New Delhi - 110034

E-Mail - ufe126@gmail.com, Web Site : www.lifeguardindia.in

PRICE LIST

w.e.f. April 01st, 2025

POWDER PORTABLE FIRE EXTINGUISHERS STORED PRESSURE TYPE (IS: 15683)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-121	Powder Fire Extinguisher (Stored Pressure type) Capacity 01 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	1,750.00
2.	LG- 122	Powder Fire Extinguisher (Stored Pressure type) Capacity 02 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	2,100.00
3.	LG-124	Powder Fire Extinguisher (Stored Pressure type) Capacity 04 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	3,000.00
4.	LG-126	Powder Fire Extinguisher (Stored Pressure type) Capacity 06 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	3,625.00
5.	LG-129	Powder Fire Extinguisher (Stored Pressure type) Capacity 09 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder complete with squeeze grip release valve, discharge pipe locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	4,875.00

PREMIUM POWDER PORTABLE FIRE EXTINGUISHERS STORED PRESSURE TYPE (IS: 15683)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-121P	PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 01 Kg duly ISI marked conforming to IS: 15683:2018 , HLD (Helium Leak Detection) Tested, with UL Listed ABC MAP 90% powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	2,750.00
2.	LG- 122P	PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 02 Kg duly ISI marked conforming to IS: 15683:2018 , HLD (Helium Leak Detection) Tested, with UL Listed ABC MAP 90% powder complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	3,500.00
3.	LG-124P	PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 04 Kg duly ISI marked conforming to IS: 15683:2018 , HLD (Helium Leak Detection) Tested, with UL Listed ABC MAP 90% powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	5,700.00
4.	LG-126P	PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 06 Kg duly ISI marked conforming to IS: 15683:2018 , HLD (Helium Leak Detection) Tested, with UL Listed MAP 90% ABC powder complete with squeeze grip release valve, discharge pipe, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	8,125.00
5.	LG-129P	PREMIUM Powder Fire Extinguisher (Stored Pressure type) Capacity 09 Kg duly ISI marked conforming to IS: 15683:2018 , HLD (Helium Leak Detection) Tested, with UL Listed ABC MAP 90% powder complete with squeeze grip release valve, discharge pipe locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	12,000.00

POWDER PORTABLE FIRE EXTINGUISHERS GAS CARTRIDGE TYPE (IS: 15683)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-224	Powder Fire Extinguisher (Gas Cartridge type) Capacity 04 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder; Complete with IS 4947 ISI marked Gas Cartridge with squeeze grip release valve, discharge pipe, locking arrangement, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	4,875.00
2.	LG-226	Powder Fire Extinguisher (Gas Cartridge type) Capacity 06 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder; Complete with IS 4947 ISI marked Gas Cartridge with squeeze grip release valve, discharge pipe, locking arrangement, operation manual and bracket. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	5,700.00
3.	LG-229	Powder Fire Extinguisher (Gas Cartridge type) Capacity 09 Kg duly ISI marked conforming to IS: 15683:2018 , with IS 4308, ISI marked ABC powder; Complete with IS 4947 ISI marked Gas Cartridge with squeeze grip release valve, discharge pipe locking arrangement, operation manual and bracket. Operating Temperature -30°C to + 60°C. Brand LIFEGUARD	8424/18%	6,875.00

***Also Available in ISI marked BC Powder IS: 4308, MAP 90% ISI marked ABC Powder or UL Listed MAP 90% ABC Powder.**

POWDER WHEELED TYPE FIRE EXTINGUISHER (IS: 16018)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-1225	Powder Wheeled Fire Extinguisher Capacity 25 Kg Stored pressure type duly ISI marked conforming to IS: 16018 with rotary release valve, delivery hose, shut-off valve fitted with discharge nozzle & IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	16,000.00
2.	LG-2225	Powder Wheeled Fire Extinguisher Capacity 25 Kg duly ISI marked conforming to IS: 16018 with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & 300 gm CO₂ gas cartridge , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to +55°C. Brand LIFEGUARD	8424/18%	15,500.00
3.	LG-3225	Powder Wheeled Fire Extinguisher Capacity 25 Kg duly ISI marked conforming to IS: 16018 with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & outer CO₂ cylinder , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	21,500.00
4.	LG-3250	Powder Wheeled Fire Extinguisher Capacity 50 Kg duly ISI marked conforming to IS: 16018 with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & outer CO₂ cylinder , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	31,250.00
5.	LG-3275	Powder Wheeled Fire Extinguisher Capacity 75 Kg duly ISI marked conforming to IS: 16018 with G.M. Cap, delivery hose, shut-off valve fitted with discharge nozzle & outer CO₂ cylinder , IS 4308, ISI marked BC Powder, Complete in all respect. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	37,500.00

*** Also Available in ABC Powder, IS: 4308**

ABC MODULAR TYPE FIRE EXTINGUISHERS CE CERTIFIED

S. No.	LG-CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-1602	ABC Modular Type CE certified Capacity 2 Kg Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. Brand LIFEGUARD	8424/18%	2,750.00
2.	LG-1605	ABC Modular Type CE certified Capacity 5 Kg Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. Brand LIFEGUARD	8424/18%	4,250.00
3.	LG-1610	ABC Modular Type CE certified Capacity 10 Kg Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. Brand LIFEGUARD	8424/18%	5,875.00
4.	LG-1615	ABC Modular Type CE certified Capacity 15 Kg Fire Extinguisher filled with ISI marked IS: 4308 ABC Powder. Complete in all respect. Brand LIFEGUARD	8424/18%	8,750.00

*** Also available in UL Listed MAP90% ABC powder.**

CO₂ PORTABLE FIRE EXTINGUISHERS (IS: 15683)

S. No.	LG-CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-132	CO₂ type Fire Extinguisher ISI marked conforming to IS: 15683. Capacity 2 Kg. Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to +60°C. Brand LIFEGUARD	8424/18%	7,000.00
2.	LG-133	CO₂ type Fire Extinguisher ISI marked conforming to IS: 15683. Capacity 3 Kg. Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to + 60°C. Brand LIFEGUARD	8424/18%	8,250.00
3.	LG-134	CO₂ type Fire Extinguisher ISI marked conforming to IS: 15683. Capacity 4.5 Kg. Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to +60°C. Brand LIFEGUARD	8424/18%	10,125.00

CO₂ PORTABLE LIGHT WEIGHT ALUMINUM BODY FIRE EXTINGUISHERS (IS: 15683)

S. No.	LG-CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-132AL	CO₂ type LIGHT WEIGHT ALUMINUM BODY Fire Extinguisher ISI marked conforming to IS: 15683. Capacity 2 Kg. Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to +60°C. Brand LIFEGUARD	8424/18%	9,500.00
2.	LG-134AL	CO₂ type LIGHT WEIGHT ALUMINUM BODY Fire Extinguisher ISI marked conforming to IS: 15683. Capacity 4.5 Kg. Complete with delivery hose horn, wheel type release valve, locking arrangement, operation manual and bracket. Operating Temperature: - 30°C to +60°C. Brand LIFEGUARD	8424/18%	15,500.00

CO₂ WHEELED TYPE FIRE EXTINGUISHER (IS:16018)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-336	CO₂ Wheeled Fire Extinguisher ISI marked conforming to IS: 16018. Capacity 6.5 Kg. Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	17,500.00
2.	LG-339	CO₂ Wheeled Fire Extinguisher ISI marked conforming to IS: 16018. Capacity 9 Kg. Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: -30°C to + 55°C. Brand LIFEGUARD	8424/18%	20,500.00
3.	LG-3322	CO₂ Wheeled Fire Extinguisher ISI marked conforming to IS: 16018. Capacity 22.5 Kg. Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	35,000.00
4.	LG-3345	CO₂ Wheeled Fire Extinguisher. Capacity 45 Kg. Complete with composite trolley with handle & wheel, operation manual, wheel type release valve, locking arrangement and shut-off valve fitted with delivery hose horn. Operating Temperature: - 30°C to + 55°C. Brand LIFEGUARD	8424/18%	67,500.00

WATER PORTABLE FIRE EXTINGUISHERS (IS: 15683)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-106	Water Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683. Capacity 6 litre. Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	2,625.00

2.	LG- 109	Water Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683 . Capacity 9 litre . Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	3,125.00
3.	LG-206	Water Fire Extinguisher Gas Cartridge type ISI marked conforming to IS: 15683 . Capacity 6 litre . Complete with IS: 4947 Gas Cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	4,625.00
4.	LG-209	Water Fire Extinguisher Gas Cartridge type ISI marked conforming to IS: 15683 . Capacity 9 litre . Complete with IS: 4947 Gas Cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	5,125.00

WATER WHEELED TYPE FIRE EXTINGUISHERS (IS: 16018)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG- 1020	Water Wheeled Fire Extinguisher ISI marked conforming to IS: 16018 Stored pressure type with rotary release valve, delivery hose, shut-off valve fitted with discharge nozzle. Complete in all respect. Capacity 20 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	13,500.00
2.	LG-2020	Water Wheeled Fire Extinguisher ISI marked conforming to IS: 16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & CO₂ gas cartridge . Complete in all respect. Capacity 20 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	13,000.00
3.	LG-2045	Water Wheeled Fire Extinguisher ISI marked conforming to IS: 16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & CO₂ gas cartridge . Complete in all respect. Capacity 45 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	15,500.00
4.	LG-2060	Water Wheeled Fire Extinguisher ISI marked conforming to IS: 16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & CO₂ gas cartridge . Complete in all respect. Capacity 60 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	17,500.00
5.	LG-3045	Water Wheeled Fire Extinguisher ISI marked conforming to IS: 16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & outer CO₂ Cylinder . Complete in all respect. Capacity 45 litre . Operating Temperature: + 5°C to + 55°C. Brand LIFEGUARD	8424/18%	22,500.00
6.	LG-3060	Water Wheeled Fire Extinguisher ISI marked conforming to IS: 16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & outer CO₂ Cylinder . Complete in all respect. Capacity 60 litre . Operating Temperature: + 5°C to + 55°C. Brand LIFEGUARD	8424/18%	23,750.00

MECHANICAL FOAM (AFFF) PORTABLE FIRE EXTINGUISHERS (IS: 15683)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-116	Mechanical Foam (AFFF) Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683 . Capacity 6 litre . Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	3,125.00
2.	LG- 119	Mechanical Foam (AFFF) Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683 . Capacity 9 litre . Complete with delivery hose, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	3,500.00

3.	LG-216	Mechanical Foam (AFFF) Fire Extinguisher Gas Cartridge type ISI marked conforming to IS: 15683 . Capacity 6 litre . Complete with gas cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	5,000.00
4.	LG-219	Mechanical Foam (AFFF) Fire Extinguisher Gas Cartridge type ISI marked conforming to IS: 15683 . Capacity 9 litre . Complete with gas cartridge, delivery hose, squeeze grip release valve, locking arrangement, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	5,500.00

MECHANICAL FOAM (AFFF) WHEELED TYPE FIRE EXTINGUISHERS (IS: 16018)

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-2120	Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked conforming to IS:16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & CO₂ gas cartridge . Complete in all respect. Capacity 20 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	14,000.00
2.	LG-2145	Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked conforming to IS:16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & CO₂ gas cartridge . Complete in all respect. Capacity 45 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	16,000.00
3.	LG-2160	Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked conforming to IS:16018 with G.M. cap, delivery hose, shut-off valve fitted with discharge nozzle & CO₂ gas cartridge . Complete in all respect. Capacity 60 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	18,000.00
4.	LG- 3145	Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked conforming to IS:16018 with G.M. cap, delivery hose, shut-off valve with discharge nozzle & outer CO₂ cylinder . Complete in all respect. Capacity 45 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	23,000.00
5.	LG- 3160	Mechanical Foam (AFFF) Wheeled Fire Extinguisher ISI marked conforming to IS:16018 with G.M. cap, delivery hose, shut-off valve with discharge nozzle & outer CO₂ cylinder . Complete in all respect. Capacity 60 litre . Operating Temperature: + 5°C to + 55°C Brand LIFEGUARD	8424/18%	25,000.00

WATER MIST TYPE FIRE EXTINGUISHERS

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-164	Water Mist Type Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683 . Capacity 4 litre . Complete with delivery hose fitted with mist forming nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	8,500.00
2.	LG-166	Water Mist Type Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683 . Capacity 6 litre . Complete with delivery hose fitted with mist forming nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	9,625.00
3.	LG-169	Water Mist Type Fire Extinguisher Stored pressure type ISI marked conforming to IS: 15683 . Capacity 9 litre . Complete with delivery hose fitted with mist forming nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	11,250.00
4.	LG-3609	Water Mist System & CAFS (COMPRESSED AIR FOAM SYSTEM) Backpack type Fire Extinguisher with aerodynamics technology from flow engineering applications involving liquid and gas mixtures, Capacity 9 Litre . Complete with delivery hose, extinguishing gun, User Manual and propellant gas cylinder filled with 2litres of compressed air. Operating Temperature: ±5°C to +60°C. Brand LIFEGUARD	8424/18%	4,50,000.00
5.	LG-3645	WHEELED TYPE Water Mist System & CAFS (COMPRESSED AIR FOAM SYSTEM) Fire Extinguisher ISI marked IS: 16018 with aerodynamics technology from flow engineering applications involving liquid and gas mixtures with the combination of the highly sophisticated Guns and a trolley supply system Capacity 45 Litre . Complete with delivery hose, extinguishing gun, User Manual and propellant gas cylinder filled with 6.8litres of compressed air. Operating Temperature: - +5°C to +60°C. Brand LIFEGUARD	8424/18%	7,25,000.00

CLEAN AGENT TYPE FIRE EXTINGUISHERS (ECO FRIENDLY) (IS: 15683)

S. No.	LG-CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-141	Clean Agent (Stored Pressure) Type Capacity 1 Kg Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Brand LIFEGUARD	8424/18%	6,100.00
2.	LG-142	Clean Agent (Stored Pressure) Type Capacity 2 Kg Fire Extinguisher ISI marked IS: 15683 filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	13,000.00
3.	LG-144	Clean Agent (Stored Pressure) Type Capacity 4 Kg Fire Extinguisher ISI marked IS: 15683 filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	24,500.00
4.	LG-146	Clean Agent (Stored Pressure) Type Capacity 6 Kg Fire Extinguisher ISI marked IS: 15683 filled with HFC 236FAClean Agent Gas. Complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect. Operating Temperature: -30°C to + 60°C. Brand LIFEGUARD	8424/18%	32,500.00

WET CHEMICAL (KITCHEN) 'F' TYPE FIRE EXTINGUISHER

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG- 154	Wet Chemical (Stored Pressure) "F" Type ISI marked IS: 15683 Capacity 4 litre Fire Extinguisher. Complete with SS body , squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect for Kitchen Fire. Brand LIFEGUARD	8424/18%	12,000.00
2.	LG-156	Wet Chemical (Stored Pressure) "F" Type ISI marked IS: 15683 Capacity 6 litre Fire Extinguisher. Complete with SS body , squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect for Kitchen Fire. Brand LIFEGUARD	8424/18%	14,000.00
3.	LG-159	Wet Chemical (Stored Pressure) "F" Type ISI marked IS: 15683 Capacity 9 litre Fire Extinguisher. Complete with SS body , squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Complete in all respect for Kitchen Fire. Brand LIFEGUARD	8424/18%	17,500.00

CLEAN AGENT MODULAR TYPE FIRE EXTINGUISHERS CE CERTIFIED

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-1702	Clean Agent Modular (ceiling mounted) Type Capacity 2 Kg CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. Brand LIFEGUARD	8424/18%	13,750.00
2.	LG-1705	Clean Agent Modular (ceiling mounted) Type Capacity 5 Kg CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. Brand LIFEGUARD	8424/18%	30,000.00
3.	LG-1710	Clean Agent Modular (ceiling mounted) Type Capacity 10 Kg CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. Brand LIFEGUARD	8424/18%	52,500.00
4.	LG-1715	Clean Agent Modular (ceiling mounted) Type Capacity 15 Kg CE certified Fire Extinguisher filled with HFC 236FAClean Agent Gas. Complete in all respect. Brand LIFEGUARD	8424/18%	85,000.00

**LION-EX® FIRE EXTINGUISHER FOR LITHIUM-ION FIRE CONTAINING HMS
(HYDRATED MICA SUSPENSION)**

S. No.	LG- CODE	DESCRIPTION	HSN CODE/ GST RATE	RATES (INR)
1.	LG-172	LION-EX® Fire Extinguisher (Stored Pressure type) Capacity 02 Ltr duly ISI marked conforming to IS: 15683:2018, with HMS (Hydrated Mica Suspension) , an Ecofriendly, Non-Toxic and Bio degradable Fire Extinguishing agent specifically for Lithium-ion Battery Fires complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	26,250.00
2.	LG-174	LION-EX® Fire Extinguisher (Stored Pressure type) Capacity 04 Ltr duly ISI marked conforming to IS: 15683:2018, with HMS (Hydrated Mica Suspension) , an Ecofriendly, Non-Toxic and Bio degradable Fire Extinguishing agent specifically for Lithium-ion Battery Fires complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	51,250.00
3.	LG-176	LION-EX® Fire Extinguisher (Stored Pressure type) Capacity 06 Ltr duly ISI marked conforming to IS: 15683:2018, with HMS (Hydrated Mica Suspension) , an Ecofriendly, Non-Toxic and Bio degradable Fire Extinguishing agent specifically for Lithium-ion Battery Fires complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	73,750.00
4.	LG-179	LION-EX® Fire Extinguisher (Stored Pressure type) Capacity 09 Ltr duly ISI marked conforming to IS: 15683:2018, with HMS (Hydrated Mica Suspension) , an Ecofriendly, Non-Toxic and Bio degradable Fire Extinguishing agent specifically for Lithium-ion Battery Fires complete with squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Operating Temperature: +5°C to + 60°C. Brand LIFEGUARD	8424/18%	1,08,750.00

D Class POWDER PORTABLE FIRE EXTINGUISHERS

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-126D	Powder Fire Extinguisher (Stored Pressure type) Capacity 06 Kg D Class powder for Metal Fire complete with specially designed applicator nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Brand LIFEGUARD	8424/18%	12,000.00
2.	LG- 129D	Powder Fire Extinguisher (Stored Pressure type) Capacity 09 Kg D Class powder for Metal Fire complete with specially designed applicator nozzle, squeeze grip release valve, locking arrangement, pressure gauge, operation manual and bracket. Brand LIFEGUARD	8424/18%	15,750.00

LANDING VALVES/ HYDRANT VALVES (IS: 5290)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-401	Gun Metal Landing Valve Single Head dia. 63 mm (Type A) ISI marked IS: 5290 with 1 no. ABS Blank Cap complete in all respect Brand LIFEGUARD	7412/18%	18,500.00
2.	LG-402	Stainless Steel Landing Valve Single Head dia. 63 mm (Type A) ISI marked IS: 5290 with 1 no. ABS Blank Cap complete in all respect Brand LIFEGUARD	7307/18%	9,500.00
3.	LG-406	Gun Metal Landing Valve Double Head dia. 63 mm (Type B) ISI marked IS: 5290 with 2 no. ABS Blank Caps complete in all respect Brand LIFEGUARD	7412/18%	45,000.00
4.	LG-407	Stainless Steel Landing Valve Double Head dia. 63 mm (Type B) ISI marked IS: 5290 with 2 no. ABS Blank Caps complete in all respect Brand LIFEGUARD	7307/18%	21,000.00

FIRE HOSE DELIVERY COUPLING, BRANCH PIPE AND NOZZLE (IS: 903)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-411	Gun Metal Branch Pipe dia.63 mm & nozzle 20 mm ISI marked IS 903 complete in all respect Brand LIFEGUARD	7412/18%	6,500.00
2.	LG-412	Stainless Steel Branch Pipe dia.63 mm & nozzle 20 mm ISI marked IS 903 complete in all respect Brand LIFEGUARD	7307/18%	3,125.00
3.	LG-413	Aluminum Alloy Branch Pipe dia.63 mm & nozzle 20 mm ISI marked IS 903 complete in all respect Brand LIFEGUARD	7609/18%	1,850.00
4.	LG-416	Gun Metal Fire Hose Delivery Coupling (MALE/ FEMALE) dia. 63 mm ISI marked IS 903 complete in all respect Brand LIFEGUARD	7412/18%	7,125.00

5.	LG-417	Stainless Steel Fire Hose Delivery Coupling (MALE/FEMALE) dia. 63 mm ISI marked IS 903 complete in all respect Brand LIFEGUARD	7307/18%	3,500.00
6.	LG-418	Aluminum Alloy Fire Hose Delivery Coupling (MALE/FEMALE) dia. 63 mm ISI marked IS 903 complete in all respect Brand LIFEGUARD	7609/18%	2,000.00

FIRE HOSE BOXES

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-501A	Hose box (Single Door) (500mm x 500mm x 250mm) 18 gauge suitable for 1 no. 15mtr. Hose and 1 no short branch pipe. Complete in all respect Brand LIFEGUARD	7310/18%	4,500.00
2.	LG-501G	Hose box (Double Door) (750mm x 600mm x 250mm) 18 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe. Complete in all respect Brand LIFEGUARD	7310/18%	6,000.00
3.	LG-501C	Hose box (Double Door) (750mm x 600mm x 250mm) 16 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe. Complete in all respect Brand LIFEGUARD	7310/18%	7,000.00
4.	LG-501D	Hose box (Double Door) (900mm x 600mm x 500mm) 16 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe and 1 no hydrant. Complete in all respect Brand LIFEGUARD	7310/18%	15,000.00
5.	LG-501H	Hose box (Double Door) (900mm x 600mm x 500mm) 18 gauge suitable for 2 no. 15mtr. Hose and 1 no short branch pipe and 1 no hydrant. Complete in all respect Brand LIFEGUARD	7310/18%	12,750.00
6.	LG-501E	Fire hose cabinet door (40mm x 40mm x 5mm) angle depth fabricated with 2100mm x 1200mm MS sheet. Complete in all respect Brand LIFEGUARD	7310/18%	20,000.00
7.	LG-501F	Fire hose cabinet door (40mm x 40mm x 5mm) angle depth fabricated with 2100mm x 900mm MS sheet. Complete in all respect Brand LIFEGUARD	7310/18%	18,000.00

FIRST AID HOSE REEL (IS: 884)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-421	Manual Swing type fire hose reel ISI marked IS: 884 with Thermoplastic hose pipe 30mtr. Long, dia 20mm, ISI marked IS: 12585 with GM shut off nozzle complete in all respect Type II (W.P. 10.2 Kg/cm ²). Brand LIFEGUARD	8424/18%	11,750.00
2.	LG-421A	Shut-Off Nozzle (Gun Metal) for Hose Reel. Brand LIFEGUARD	7412/18%	1000.00
3.	LG-421B	Hose pipe 30mtr. Long, dia 20mm ISI marked Brand LIFEGUARD 1. Thermoplastic hose pipe Type I (W.P. 7.2 Kg/cm ²) IS : 12585 2. Thermoplastic hose pipe Type II (W.P. 10.2 Kg/cm ²) IS : 12585 3. Rubber hose pipe Type II (W.P. 10.2 Kg/cm ²) IS : 444	3917/18% 3917/18% 4009/18%	3,750.00 4,125.00 4,750.00
4.	LG-421C	Manual Swing type fire Hose Reel Drum ISI marked IS:884 Brand LIFEGUARD.	8424/18%	6,750.00
5.	LG-421D	Compact Hose Reel Imported type with company fitted accessories, complete in all respect. Brand LIFEGUARD	8424/18%	11,000.00

FIRE HOSES FOR HYDRANT SYSTEM

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-422A	Reinforced Rubber Lined (RRL) Fire Hose Type 1 ISI marked conforming to IS: 636, 15mtr long with ISI marked Gun Metal Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	10,000.00
2.	LG-422I	Reinforced Rubber Lined (RRL) Fire Hose Type 2 ISI marked conforming to IS: 636, 15mtr long with ISI marked Gun Metal Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	10,500.00
3.	LG-422B	Reinforced Rubber Lined (RRL) Fire Hose Type 3 ISI marked conforming to IS: 636, 15mtr long with ISI marked Gun Metal Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	15,000.00

4.	LG-422C	Reinforced Rubber Lined (RRL) Fire Hose Type 1 ISI marked conforming to IS: 636, 15mtr long with ISI marked Stainless Steel Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	8,000.00
5.	LG-422 J	Reinforced Rubber Lined (RRL) Fire Hose Type 2 ISI marked conforming to IS: 636, 15mtr long with ISI marked Stainless Steel Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	8,375.00
6.	LG-422D	Reinforced Rubber Lined (RRL) Fire Hose Type 3 ISI marked conforming to IS: 636, 15mtr long with ISI marked Stainless Steel Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	13,500.00
7.	LG-422E	Reinforced Rubber Lined (RRL) Fire Hose Type 1 ISI marked conforming to IS: 636, 30mtr long with ISI marked Gun Metal Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	15,500.00
8.	LG-422F	Reinforced Rubber Lined (RRL) Fire Hose Type 1 ISI marked conforming to IS: 636, 30mtr long with ISI marked Stainless Steel Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	14,500.00
9.	LG-422G	Controlled Percolating (CP) Fire Hose ISI marked conforming to IS: 8423, 15mtr long with ISI marked Gun Metal Coupling dia 63 mm with GI Binding. Brand LIFEGUARD	5909/12%	9,625.00
10.	LG-422H	Controlled Percolating (CP) Fire Hose ISI marked conforming to IS: 8423, 15mtr long with ISI marked Stainless Steel Coupling dia 63 mm. Brand LIFEGUARD	5909/12%	7,750.00

WATER / FOAM MONITORS

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-526 0063	Water Monitor 63mm dia to be operated in pressure line with 7-12 Kg/cm ² , Inlet Flange NB 75 mm. Flow of 1750lpm with throw range of up to 52Mtrs at angle of 30°c. Brand LIFEGUARD	8424/18%	30,000.00
2.	LG-526 0075	Water Monitor 75mm dia to be operated in pressure line with 7-12 Kg/cm ² , Inlet Flange NB 100 mm. Flow of 2580lpm with throw range of up to 62Mtrs at angle of 30°c. Brand LIFEGUARD	8424/18%	42,500.00
3.	LG-526 0100	Water Monitor 100mm dia to be operated in pressure line with 7-12 Kg/cm ² , Inlet Flange NB 150 mm. Flow of 3750lpm (with manual) throw range up to 67Mtrs at angle of 30°c. Brand LIFEGUARD	8424/18%	67,500.00
4.	LG-526 1063	Foam Monitor 63mm dia to be operated in pressure line with 7-12 Kg/cm ² , Inlet Flange NB 75 mm with FB 5X Nozzle. Brand LIFEGUARD	8424/18%	50,000.00
5.	LG-526 1075	Foam Monitor 75mm dia to be operated in pressure line with 7-12 Kg/cm ² , Inlet Flange NB 100 mm with Aqua Nozzle. Brand LIFEGUARD	8424/18%	1,70,000.00

FIRE BRIGADE CONNECTION

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-423B	Two way Fire brigade connection dia 63mm. complete in all respect. Brand LIFEGUARD	7412/18%	9,500.00
2.	LG-423C	Three way Fire brigade connection dia 63mm. complete in all respect. Brand LIFEGUARD	7412/18%	11,750.00
3.	LG-423A	Four way Fire brigade connection dia 63mm. complete in all respect. Brand LIFEGUARD	7412/18%	18,500.00
4.	LG-502	Draw out connection. complete in all respect. Brand LIFEGUARD	7412/18%	7,500.00
5.	LG-517	Air Release Valve. Brand LIFEGUARD	7412/18%	2,250.00

AUTOMATIC SPRINKLERS

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-503B	Pendent type automatic sprinkler (ISI MARKED) (LIFEGUARD)	8424/12%	292.50
2.	LG-503D	Upright type automatic sprinkler (ISI MARKED) (LIFEGUARD)	8424/12%	292.50
3.	LG-503F	Side wall type automatic sprinkler (ISI MARKED) (LIFEGUARD)	8424/12%	325.00
4.	LG-541	Water Curtain Nozzle (15 mm)	8424/18%	700.00
5.	LG-541	Water Curtain Nozzle (25 mm)	8424/18%	950.00

FIRE DETECTION SYSTEMS & ACCESSORIES

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-521 SD	Smoke Detector with 360° identification in alarm condition.	8531/18%	1,775.00
2.	LG-521 RD	Heat Detector CUM ROR with 360° identification in alarm condition.	8531/18%	1,925.00
3.	LG-521 HD	Heat Detector with 360° identification in alarm condition.	8531/18%	1,837.50
4.	LG-521 MD	Multi-criteria Detector with 360° identification in alarm condition.	8531/18%	1,900.00
5.	LG-545 II	2-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	8,625.00
6.	LG-545 IV	4-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	11,200.00
7.	LG-545 VI	6-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	16,950.00
8.	LG-545 VIII	8-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	19,975.00
9.	LG-545 X	10-Zone Fire Alarm Control Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	22,425.00
10.	LG-520A	Manual call Point (MCP) ABS. Brand LIFEGUARD	8531/18%	575.00
11.	LG-520B	Hooter (MS) 24 Volt ABS. Brand LIFEGUARD	8531/18%	725.00
12.	LG-520C	Response Indicator ABS. Brand LIFEGUARD	8531/18%	205.00

TOTAL GAS FLOODING PANEL

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-546 II	2-Zone Total Gas Flooding Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	16,525.00
2.	LG-546 IV	4-Zone Total Gas Flooding Panel Complies to IS 2189:1999 and Tested by ERTL (N), 2 x 16 character backlit LCD display, NO/NC contacts for both fire and fault. Brand LIFEGUARD	8531/18%	30,000.00

WEIGHT SURVEILLANCE MODULE (CO₂, FM-200, NOVEC etc.)

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG - 611A	Weight Surveillance Module Max Wt. 200 KG , with collar and necessary cables. Brand LIFEGUARD	8423/18%	19,625.00
2.	LG - 611B	Weight Surveillance Module Max Wt. 500 KG , with collar and necessary cables. Brand LIFEGUARD	8423/18%	20,375.00
3.	LG - 611C	Weight Surveillance Module Max Wt. 200 KG , with platform, collar and necessary cables. Brand LIFEGUARD	8423/18%	20,125.00
4.	LG - 611D	Weight Surveillance Module Max Wt. 500 KG , with platform, collar and necessary cables. Brand LIFEGUARD	8423/18%	20,750.00

ACTOK LIFEGUARD STICKER & CORD

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG - 560	Supply of Fire Suppression Sticker with composite material being a mixture of microcapsules with a heating compound. Operating Temperature 150°C , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, Capacity: 0.2 Units	8424/18%	2,062.50
2.	LG - 56015	Supply of Fire Suppression Sticker with composite material being a mixture of microcapsules with a heating compound. Operating Temperature 150°C , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate	8424/18%	11,750.00

		from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, Capacity: 15 Units		
3.	LG - 56025	Supply of Fire Suppression Sticker with composite material being a mixture of microcapsules with a heating compound. Operating Temperature 150°C , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, Capacity: 25 Units	8424/18%	17,250.00
4.	LG - 56045	Supply of Fire Suppression Sticker with composite material being a mixture of microcapsules with a heating compound. Operating Temperature 150°C , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, Capacity: 45 Units	8424/18%	23,750.00
5.	LG - 56065	Supply of Fire Suppression Sticker with composite material being a mixture of microcapsules with a heating compound. Operating Temperature 150°C , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue Protection Class: IP20, Capacity: 65 Units	8424/18%	37,500.00
6.	LG - 561	Digital Linear Heat Detector Cord with composite material being a mixture of microcapsules with a heating compound. Operating Temperature 150°C , Ambient Temperature from -50°C to +80°C. Warranty period 5 years & ISO 9000:2011, ISO 9001:2015, en Approval WBO/8/I/CNBOP-PIB 2015 Edition 2 (Europe), Test Certificate from competent authority etc. Ambient/ Operating Temperatures:-50°C to +80°C. Shelf Life: 60 Months from the date of Issue. Complete with all necessary installation accessories (cable & insulations) for protection cover of connecting teeth.	8424/18%	24,750.00

EMERGENCY LIGHTS

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG - 641	EMERGENCY LIGHT providing through 16Watt Twin UL Listed High Intensity LED fitted Lamps with Adjustable Swivel Type Beam Lights fitted upon Powder Coated CRCA/MS Sheet Sleek Electronic Cabinet with Customized Signage fitted with 12V, 7AH SMF Battery giving Battery Backup of Upto 5 Hours provided with feature of Trickle Charging facilitating Overcharging and Low Battery Protection. 4 nos. UL certified Dual Tone LEDs with CRI Index greater than 90 provide maximum Smoke Penetration from each Lamp. Certificate of UL listed LED used are provided with each unit of Emergency Light. Electrical Supply is suitable for 230V 50Hz AC fitted with Fuse safety. Brand LIFE GUARD	8513/18%	6,250.00
2.	LG - 642	EGRESS EDGELIT LIGHT with customizable print and color, with backup of 2-3 hours on battery. Brand LIFE GUARD Single Side (per sq. inch.) Red/Green LED Double Side (per sq. inch.) Red/Green LED	8513/18%	53.75 68.75
3.	LG - 642A	EGRESS EDGELIT LIGHT with customizable print and color, without battery backup. Brand LIFE GUARD Single Side (per sq. inch.) Red/Green LED Double Side (per sq. inch.) Red/Green LED	8531/18%	47.50 62.50
4.	LG-528	Photoluminescence Emergency Glow signage, as per specification. Brand LIFE GUARD 1. With aluminum Base (per. Sq. inch) Single Side 2. With aluminum Base (per. Sq. inch) Double Side 3. With Acrylic Base (per. Sq. inch) Single Side 4. With aluminum Base (per. Sq. inch) Double Side	8310/18%	20.00 40.00 18.75 37.50

ALGORITHMIC ADDRESSABLE FIRE DETECTION SYSTEM

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-CLOYN02 BING	The C-LYON Algorithmic Control Panel is EN 54-2 and EN 54-4 according to the latest CE Directives/Regulation. Configurable with 2 loops. Loop Capability 99 points. Capacity of 4095 events with date and time. Backlit LCD display with 4 lines and 40 characters. Configurable with the PC-EASY Co-NET software. Allows connections of up to 8 repeaters and/or 8 control panels on network.	8531/18%	1,01,625.00
2.	LG-ZAFIRO 2 BING	The ZAFIR Algorithmic Control Panel is EN 54-2 and EN 54-4 according to the latest CE Directives/Regulation. Configurable with 2 loops. Loop Capability 199 points. Capacity of 4095 events with date and time. Backlit LCD display with 4 lines and 40 characters. Configurable with the PC-EASY Co-NET software. Allows connections of up to 8 repeaters and/or 8 control panels on network.	8531/18%	1,56,500.00

3.	LG-LYONING	The LYON Algorithmic Control Panel is EN 54-2 and EN 54-4 according to the latest CE Directives/Regulation. Configurable with 4 loops and expandable up to 20 loops Loop Capability 199 points. Capacity of 4095 events with date and time. Backlit LCD display with 4 lines and 40 characters. Configurable with the PC-EASY Co-NET software. Allows connections of up to 8 repeaters and/or 8 control panels on network.	8531/18%	2,24,700.00
4.	LG-ZYR	Repeater Panel for LYON, C.LYON and ZAFIR Connect up to 15 repeaters No supply required up to 3 repeaters	8531/18%	1,26,875.00
5.	LG- A30XTA	Algorithmic Addressable Heat Sensor for fire detection. The A30XTA is capable of registering absolute temperatures (heat sensor) but also temperature rise (ROR). Two red LED in alarm condition. Identification from any direction (360°). Easy connection, without polarity.	8531/18%	4,800.00
6.	LG-A3XHAS	Algorithmic Addressable Smoke Sensor for fire detection. The sensor A30XHAS has an optical smoke sensor. Two Red LED in alarm condition. Identification from any direction (360°).	8531/18%	4,875.00
7.	LG-A30XHA	Algorithmic Addressable Multi-criteria Sensor for fire detection. The sensor A30XHA has an optical smoke sensor and also has a static heat element that sets it into alarm status when temperature reaches 55° C. Two Red LED in alarm condition. Identification from any direction (360°).	8531/18%	5,200.00
8.	LG- PUCAY	Resettable Manual Call Point (with short-circuit isolator) for algorithmic addressable detection systems. Easily resettable call point by pushing yellow button on the front side. Transparent protector cover to avoid accidental false alarms.	8531/18%	4,375.00
9.	LG- MSTAY	Monitor Module - Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The Master Detection Module is placed in a rectangular, heat-resistant ABS box.	8531/18%	6,125.00
10.	LG- MDA1Y	Relay Module -Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The device is placed in a rectangular heat-resistant ABS box.	8531/18%	8,562.50
11.	LG- MDA2Y	Relay Module(II) -Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The device is placed in a rectangular heat-resistant ABS box.	8531/18%	9,312.50
12.	LG-KMAY	Supervision Module Microprocessor based algorithmic addressable device (with short-circuit isolator) installed as another element inside the loop. The Relay and technical signal Module is placed in a rectangular, head-resistant ABS box.	8531/18%	7,125.00
13.	LG-MYOA	Input/output Module Microprocessor based algorithmic element installed as another element inside the loop (It is not addressable – there is no need to configure this element). The element is feed from the loop connection	8531/18%	11,700.00
14.	LG-KABY	Loop Isolator Module Microprocessor based digital and addressable device (with short-circuit isolator) installed as another element inside the loop. The sounder is made of in ABS heat-resistant plastic red color. Standard configuration of the light signal at the base of the sounder SIRAY+BSLC according to EN 54-23	8531/18%	5,625.00
15.	LG-SIRAY	Addressable Loop Sounder • 32 Selectable Tones • Low Current Consumption • Automatic Synchronization	8531/18%	12,375.00
16.	LG-SIRAYL	Addressable Loop Sounder and Flasher • 32 Selectable Tones • Low Current Consumption • Automatic Synchronization	8531/18%	12,600.00

CO₂ GAS CARTRIDGE FOR FIRE EXTINGUISHERS (IS: 4947)

S. No.	LG-CODE	DESCRIPTION	HSN CODE / GST RATE	RATES (INR)
1.	LG-2506	CO ₂ Gas cartridge ISI Marked IS 4947. Capacity 60gms. Brand LIFEGUARD	8424/18%	500.00
2.	LG-2512	CO ₂ Gas cartridge ISI Marked IS 4947. Capacity 120gms. Brand LIFEGUARD	8424/18%	600.00
3.	LG-2520	CO ₂ Gas cartridge ISI Marked IS 4947. Capacity 200gms. Brand LIFEGUARD	8424/18%	750.00
4.	LG-2530	CO ₂ Gas cartridge Capacity 300gms. Brand LIFEGUARD	8424/18%	1,125.00
5.	LG-2550	CO ₂ Gas cartridge Capacity 500gms. Brand LIFEGUARD	8424/18%	1,500.00

FIRE FIGHTING CHEMICAL AND REFILLS

S. No.	LG- CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-553	Dry powder for A, B&C Class of fire ISI marked MAP 50% IS:4308	8424/18%	175.00 Per Kg
2.	LG-553	Dry powder for A, B&C Class of fire ISI marked MAP 90%	8424/18%	400.00 Per Kg
3.	LG-720	Dry powder for A, B&C Class of fire UL listed MAP 90%. Brand LIFEGUARD	8424/18%	650.00 Per Kg
4.	LG-552	Dry powder for B&C Class of fire ISI marked IS:4308	8424/18%	65.00 Per Kg
5.	LG-553A	Dry powder for A, B&C Class of fire	8424/18%	162.50 Per Kg
6.	LG-551	Foam concentrated for producing mechanical foam for firefighting type -6%. Capacity 540 ml.	8424/18%	150.00 Each
7.	LG-551A	Foam concentrated for producing mechanical foam for firefighting type -6%. Capacity 3litre.	8424/18%	650.00 Each
8.	LG-551B	Foam concentrated for producing mechanical foam for firefighting type -6%. Capacity 20litre.	8424/18%	2500.00 Each
9.	LG-551C	Foam concentrated for producing mechanical foam for firefighting type -3%. Capacity 540 ml.	8424/18%	200.00 Each
10.	LG-551D	Foam concentrated for producing mechanical foam for firefighting type -3%. Capacity 3litre.	8424/18%	750.00 Each
11.	LG-551E	Foam concentrated for producing mechanical foam for firefighting type -3%. Capacity 20litre.	8424/18%	2,750.00 Each
12.	LG-551F	Foam concentrated for producing mechanical foam for firefighting UL Listed	8424/18%	275.00 Per liter

MISCELLANEOUS FIRE FIGHTING ACCESSORIES

S. No.	LG-CODE	DESCRIPTION	HSN CODE /GST RATE	RATES (INR)
1.	LG-549	Fire Rescue Kit , equipped with emergency response material, contained in a mild steel box (460X380X165) mm with texture finish to with-stand all weather conditions containing 1 whistle, 1 safety torch, 1 Fire blanket, 1 Respiratory Oxygen Reserver set for Resuscitator with Multi Gas Filters, 1 Smoke mask & 1 Fireman Axe. Brand LIFEGUARD	7310/18%	87,500.00
2.	LG-525P	Heavy-Duty Leak-Proof ISI Marked Fire Bucket made of Mild Steel conforming IS 2546:1974 Capacity 10 Liter. Brand LIFEGUARD	7310/18%	1,750.00
3.	LG-525	Fire Bucket MS Capacity 9/ 10 liter. Brand LIFEGUARD	7310/18%	750.00
4.	LG-525C	Fire Bucket Commercial.	7310/18%	500.00
5.	LG-525A	Fire Bucket Stand suitable for 4 buckets. Brand LIFEGUARD	7308/18%	1,375.00
6.	LG-525B	Fire Bucket Stand suitable for 6 buckets. Brand LIFEGUARD	7308/18%	2,375.00
7.	LG-525AC	Fire Bucket Stand with Canopy suitable for 4 buckets. Brand LIFEGUARD	7308/18%	6,000.00
8.	LG-525BC	Fire Bucket Stand with Canopy suitable for 6 buckets. Brand LIFEGUARD	7308/18%	7,000.00
9.	LG-534	Fire Extinguisher Stand. Brand LIFEGUARD 1. M.S. (Round Shape) 2. S.S. (Round Shape)	7308/18%	750.00 750.00
10.	LG-54007	Flexible Hose for sprinklers with fitting UL listed 700MM	7307/18%	1,250.00
11.	LG-54010	Flexible Hose for sprinklers with fitting UL listed 1000MM	7307/18%	1,350.00
12.	LG-54012	Flexible Hose for sprinklers with fitting UL listed 1200MM	7307/18%	1,450.00
13.	LG-54015	Flexible Hose for sprinklers with fitting UL listed 1500MM	7307/18%	1,650.00
14.	LG-54018	Flexible Hose for sprinklers with fitting UL listed 1800MM	7307/18%	2,200.00
15.	LG-538	Fireman axe	8205/18%	875.00
16.	LG-530	Fire hook without bamboos.	8205/18%	425.00
17.	LG-531	Fire beater without bamboos.	8205/18%	625.00
18.	LG-532	Shovel with wooden handle.	4417/12%	1,750.00
19.	LG-527A	Mobile Foam Unit with Variable Inline Inductor, Nozzle, 2 No's RRL Hose And 20litre X 4pc AFFF Foam. Complete in all respect as per PGC Drawing.	7310/18%	1,12,500.00
20.	LG-527B	M.S tank Mobile Foam Unit capacity 100 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	1,12,500.00
21.	LG-527C	M.S tank Mobile Foam Unit capacity 200 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	1,62,500.00
22.	LG-527D	S.S tank Mobile Foam Unit capacity 100 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	1,62,500.00
23.	LG-527E	S.S tank Mobile Foam Unit capacity 200 liter along with Inline inductor, nozzle, 2 No's RRL Hose. Complete in all respect.	7310/18%	2,25,000.00

24.	LG-527A	G.M. Variable Inline Inductor with pickup tube & inbuilt NRV to foam inlet	7412/18%	26,250.00
25.	LG-518A	Electric siren 1 1/2 km 220 V Brand LIFEGUARD	8531/18%	4,000.00
26.	LG-518B	Electric siren 1 km 220 V Brand LIFEGUARD	8531/18%	6,000.00
27.	LG-518C	Electric siren 1 1/2 km 220 V Brand LIFEGUARD	8531/18%	11,000.00
28.	LG-518D	Electric siren 2 km 220 V Double Mounting Brand LIFEGUARD	8531/18%	20,000.00
29.	LG-519E	Electric siren 3 km 220 V Double Mounting Brand LIFEGUARD	8531/18%	35,000.00
30.	LG-519A	Hand operated siren 1 1/2 km Brand LIFEGUARD	8306/18%	7,000.00
31.	LG-519B	Hand operated siren 1 km Brand LIFEGUARD	8306/18%	9,000.00
32.	LG-519C	Hand operated siren 1 1/2 km with Stand Brand LIFEGUARD	8306/18%	17,500.00
33.	LG-543	Gum Boot	6405/18 %	1,400.00
34.	LG-524	Fireman Helmet	6506/18%	2,750.00
35.	LG-504	FB-10x with nozzle	8424/18%	13,500.00
36.	LG-505	FB-5x Nozzle pick-up tube	8424/18%	8,000.00
37.	LG-506	G.M. Dividing Breaching	7412/18%	20,000.00
38.	LG-507	G.M. Suction Strainer	7412/18%	19,750.00
39.	LG-508	G.M. Foot Valve Strainer	7412/18%	20,500.00
40.	LG-509	G.M. Suction Coupling	7412/18%	17,000.00
41.	LG-510	Revolving Branch	8424/18%	17,500.00
42.	LG-511	Fog Nozzle	8424/18%	19,250.00
43.	LG-512	Triple Purpose Nozzle	8424/18%	16,500.00
44.	LG-522	Hand Control Fast Action Nozzle	8424/18%	30,000.00
45.	LG-516	Jumbo Water Curtain Branch Nozzle (63 mm)	8424/18%	12,000.00
46.	LG-513	Double Male Coupling	7412/18%	4,500.00
47.	LG-514	Double Female Coupling	7412/18%	10,000.00
48.	LG-515A	Gun Metal Adaptor	7412/18%	3,500.00
49.	LG-515C	Stainless Steel Adaptor	7307/18%	2,500.00
50.	LG-529	G.M. Fire Bell	8306/18%	40,000.00
51.	LG-533	Rope Ladder Length 10Mtr	5609/12%	6,250.00
52.	LG-535	Fire Blanket	7019/18%	2,475.00
53.	----	Pressure Gauge Diaphragm Type	8424/18%	188.00
54.	----	ABC Valve Squeeze Grip Type	8424/18%	450.00
55.	LG-536	Pick Axe	4417/12%	1,000.00
56.	LG-523	Metal Detector	-	6,750.00
57.	LG-542	Reflective Jacket	-	875.00
58.	LG-547	Air Vessel with 8mm thick MS Sheet a) Size 250 X 1200 b) Size 250 X 2000 Brand LIFEGUARD	7310/18%	27,500.00 40,000.00

NOTE: - PLEASE REFER OUR CATALOGUE FOR LG-CODES AND THEIR CORRESPONDING PICTURES.

Terms & conditions

1. This price list cancels all our previous price lists; it is not to be treated as MRP.
2. These above rates are FOR ex-works Delhi basis.
3. GST Rates shall be charged extra as applicable on individual items.
4. Warranty: 12 months from the date of Invoice/Delivery.
5. Delivery ex-stock/ within 5 weeks after receipt of confirmed order with advance payment.
6. All our transactions are subject to Delhi jurisdiction.
7. Payment 50% advance along with confirmed order & balance before Dispatch or L/C.
8. Late Payment will be subjected to additional charges of 18% per annum of interest.
9. If any Inspection is required same shall be conducted at our works only.
10. Additional amount shall be charged if inspection is required.
11. Loading/ Unloading will be in scope of Consignee after dispatch from works.
12. HSN code/GST rates may require verification before actual implementation.
13. Cost Implication of any Services upon any of the goods will be in Buyer's Scope.
14. Prices are subject to change without any prior notice.

For **United Fire Equipments Private Limited**
sd/-
Authorized Signatory